Geosci. Instrum. Method. Data Syst. Discuss., 4, C165–C166, 2014 www.geosci-instrum-method-data-syst-discuss.net/4/C165/2014/ © Author(s) 2014. This work is distributed under the Creative Commons Attribute 3.0 License.



GID 4, C165–C166, 2014

> Interactive Comment

Interactive comment on "Auroral all-sky camera calibration" by F. Sigernes et al.

Anonymous Referee #1

Received and published: 25 September 2014

For dependable evaluation of auroral energy input, precise calibration of all-sky camera is absolutely necessary. In this paper the authors describes a two-step procedure to calibrate the sensitivity of an all-sky camera at Kejell Henriksen Observatory. The method is written in an appropriate way and understandable. Figures and Tables are well organized and helpful for understanding the context. It is a good idea to calibrate the center of image with a known brightness diffuser, and by using an integrating sphere that value is expanded to a full field of view.

However, in page 520, authors descibe that "The radiance B of the integrating sphere is per definition uniform in all directions of theta and (x,y)-points with equal R should, due to symmetry, have the same raw data count rate of u." This can be said for a freshly inside-coated integrating sphere. Beacuse coating material is higroscopic, inside of the integrating sphere will deteriorate with time, and will become not completely uniform.





I would suggest the authors that above assumption is for an ideal condition, and not necessary applied to an integrating sphere used for a long time. I recommend some minor revision or addition of a sentence.

Interactive comment on Geosci. Instrum. Method. Data Syst. Discuss., 4, 515, 2014.

GID

4, C165–C166, 2014

Interactive Comment

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

